

Uncertainty propagation in a model for the estimation of the ground level concentration of dioxin/furans emitted from a waste gasification plant

G. Ripamonti, G. Lonati, Piero Baraldi, F. Cadini, Enrico Zio

► **To cite this version:**

G. Ripamonti, G. Lonati, Piero Baraldi, F. Cadini, Enrico Zio. Uncertainty propagation in a model for the estimation of the ground level concentration of dioxin/furans emitted from a waste gasification plant. Reliability Engineering and System Safety, Elsevier, 2013, 120, pp.98-105. <10.1016/j.ress.2013.05.012>. <hal-00934518>

HAL Id: hal-00934518

<https://hal-supelec.archives-ouvertes.fr/hal-00934518>

Submitted on 22 Jan 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 Uncertainty propagation in a model for the estimation of the
2 ground level concentration of dioxin/furans emitted from a waste
3 gasification plant

4
5 G. Ripamonti & G. Lonati
6 *DIAR-Environmental Section - Politecnico di Milano, Milano, Italy*

7 P. Baraldi, F. Cadini,
8 *Dipartimento di Energia – Politecnico di Milano, Milano, Italy*

9 E. Zio
10 *Chair on Systems Science and the Energetic challenge, European Foundation for New Energy-
11 Électricité de France*
12 *Dipartimento di Energia – Politecnico di Milano, Milano, Italy*

13
14 **ABSTRACT:** In this paper we compare two approaches for uncertainty propagation in a model for
15 Environmental Impact Assessment (EIA). A purely Probabilistic (PMC) and a Hybrid probabilistic-
16 possibilistic Monte Carlo (HMC) method are considered in their application for the estimation of
17 the ground levels concentration of dioxin/furans emitted from a waste gasification plant. Under the
18 condition of insufficient information for calibrating the estimation model parameters, HMC is
19 shown to be a valid way for properly propagating parameters uncertainty to the model output, with-
20 out adopting arbitrary and subjective assumptions on the input probability distribution functions. In
21 this sense, HMC could improve the transparency of the EIA procedures with positive effects on the
22 communicability and credibility of its findings.

23 **Keywords:** Uncertainty propagation, Hybrid probabilistic-possibilistic Monte Carlo, waste gasifica-
24 tion plant, Environmental Impact Assessment.

25 **1. INTRODUCTION**

26 According to the current EU regulations (Directive 85/337/EEC as amended by Directives
27 97/11/EC and 2003/35/EC), an Environmental Impact Assessment (EIA) is required for public and
28 private projects likely to have significant impacts on the environment by virtue *inter alia* of their
29 nature, size or location. The scope of an EIA is the identification, description and assessment of a
30 project's direct and indirect effects on human beings, fauna and flora, soil, water, air, climate, land-
31 scape, material assets and cultural heritage. The EIA is a part of the decisional process for the ap-
32 proval of a proposed project. The outcomes of the EIA help orient decision makers to the priorities,
33 thus ensuring that environmental considerations are taken into account in an effective way. Fur-
34 thermore, the EIA serves an important procedural role in the overall decision-making process by
35 promoting public information and facilitating participation. This entails that an EIA be carried out
36 taking into account that its findings will be handled not only by technical experts, but also commu-
37 nicated to decision makers and stakeholders of various nature, including the local population. Since

1 in most common settings the proposed project does not meet popular consensus *a priori*, communi-
2 cability of EIA results to the involved stakeholders plays a major and challenging role. To this pur-
3 pose the EIA procedure must be open and transparent, reviewable and leading to robust and repro-
4 ducible outcomes for informed decision-making and confident public awareness.

5 With reference to the proposal of new facilities responsible of atmospheric emissions (in the present
6 work we consider a waste thermal treatment plant as an example), the EIA procedure consists of
7 three main steps (Figure 1):

- 8 a) the characterization of the source: estimation of the atmospheric emissions resulting from the
9 operation of the plant, in terms of both the nature and the quantities of pollutants;
- 10 b) the estimation of the atmospheric pollutant concentration levels in the area close to the proposed
11 new installation, by means of proper atmospheric dispersion models;
- 12 c) the assessment of the pollutant concentration levels at the receptors, resulting from the superpo-
13 sition of the estimated concentration to the existing background concentration levels.

14 The first objective of the EIA is then the demonstration that the resulting concentration levels at the
15 receptors comply with both long-term (i.e.: annual average) and short-term (i.e.: hourly and daily
16 averages) air quality limits for regulated pollutants. Secondly, as those facilities can be also respon-
17 sible for the emission of both carcinogenic and non-carcinogenic trace pollutants, as metals or diox-
18 ins and furans (PCDD/Fs) in the case of waste thermal treatment plants, additional evaluations may
19 also include human health risk assessment. This latter assessment is characterized by two main fea-
20 tures: i) a considerable complexity of the mechanisms involved and hence large related uncertain-
21 ties, ii) a general attitude of “aversion to risk”, with implications on the way uncertainties are
22 treated (Guyonnet et al., 2008).

23 The uncertainties that affect all the three steps of the EIA procedure may be originated from ran-
24 domness of the physical processes involved or from lack of precise knowledge of them. In the end,
25 regardless of the approaches and models adopted to estimate the plant emissions and their disper-
26 sion in the atmosphere, the final ambient concentrations estimates can be seriously affected by the
27 uncertainty of the values of the source term parameters and by the variability of meteorological pa-
28 rameters.

29 On the contrary, the above mentioned attitude of “aversion to risk” often leads to answering to the
30 question whether a given “acceptable” threshold may be exceeded, based on limited scenario calcu-
31 lations. In common practice, this translates in ignoring input parameter uncertainties to adopt a di-
32 rect, deterministic approach in which conservative assumptions on the scenarios and parameter val-
33 ues are made, e.g.: i) full-load plant operation and ii) concentrations of the emitted pollutants equal
34 to the regulatory limits. This approach leads to often excessively conservative results, not providing

1 a realistic and objective description of the plant impact on the environment (Lonati and Zanoni,
2 2012)

3 To overcome this problem, the EIA procedure can be framed within a probabilistic approach for i)
4 describing the uncertainties of the input parameters and ii) propagating them to the models outputs,
5 i.e.: the atmospheric pollutant concentrations. In the probabilistic approach, the uncertain variables
6 are described by means of probability distribution functions (PDFs), which are then propagated
7 through the impact assessment model by Monte-Carlo (MC) simulation according to a pure Prob-
8 abilistic Monte Carlo (PMC) method (Schuhmacher et al. 2001, Sonnemann et al. 2002, Lonati et
9 al. 2007). Nevertheless, even in the PMC approach uncertainty and variability in the atmospheric
10 dispersion model are usually neglected.

11 In general, the construction by statistical analysis of the empirical PDFs representing the uncertainty
12 in the input parameters may not be an easy task due to the scarce availability of data (Ferson and
13 Ginzburg 1996, Baudrit et al. 2006). Within a probabilistic framework, the analyst traditionally
14 solves this task forcing a subjective PDF on the scarce available data, within a Bayesian (subjective)
15 view of probabilities. This presents two major drawbacks:

- 16 - doubts may be raised on the consistency and even conservativeness of the forced PDFs, in light
17 of the incomplete/imprecise information at hand. The risk is to introduce artificial information that
18 is in fact not there;
- 19 - the subjectivity in the analysis is often neither declared nor justified, causing a loss of transpar-
20 ency in the procedure.

21 These drawbacks are of particular relevance, considering the EIA role as decision aiding and infor-
22 mative tool. A lack of transparency in the procedure can lead to a loss of credibility by the decision
23 makers and public.

24 To cope with this situation of limited information, while avoiding to introduce subjective assump-
25 tions, a number of alternative representations of uncertainty have been proposed (e.g.: fuzzy set
26 theory, evidence theory, possibility theory and interval analysis) and applied in different fields of
27 risk assessment (Klir and Yuan 1995; Aven and Zio 2011). Among them, possibility theory has re-
28 ceived growing attention because of its representation power and its relative mathematical simplic-
29 ity. In recent past years some applications of these alternative approaches have been exploited also
30 in the environmental risk assessment field (Guyonnet et al. 2003, Kentel and Aral 2005, Li et al.
31 2007, Kumar et al. 2009).

32 In practice, different input parameters of the same model may be characterized by different amounts
33 of information availability, thus possibly giving rise to both probabilistic and possibilistic uncer-
34 tainty representations. In this regard, Hybrid probabilistic-possibilistic Monte Carlo methods

1 (HMC) have been recently proposed for combining both representation frameworks in the same un-
2 certainty propagation analysis (Baudrit et al. 2006, Baraldi and Zio, 2008, Flage et al. 2010).

3 In this work, the uncertainty representation and propagation problems are considered with reference
4 to the first two steps of the EIA procedure (i.e.: emission estimation and atmospheric dispersion).

5 For ease of illustration, we make reference to a case study concerning the project of a new waste
6 gasification plant. The plant, designed for a daily waste throughput of 900 metric tons, has been re-
7 cently proposed for realization in the South-East of the city of Milan, Italy and is subject to the re-
8 quirement of EIA for its potential impact on air quality.

9 The focus of the analysis is on dioxins and furans (PCDD/Fs) since the thermal treatment of waste
10 is a well-known source of PCDD/Fs to the atmosphere (Domingo et al. 2002, Schuhmacher and
11 Domingo 2006) and these pollutants have a relevant role in health risk assessment due to their car-
12 cinogenic potential and to their persistency in the environment, once released into the atmosphere
13 (Travis and Hattemer-Frey 1991, Mukerjee 1998).

14 The final objective of the work is the assessment of the contribution to PCDD/Fs long-term concen-
15 tration (i.e.: annual average) in the ambient air in the surroundings of the proposed plant due to the
16 flue gas emissions released at the stack of the plant. This information, other than a direct informa-
17 tion on the environmental impact of plant emissions, is also the basic input for the subsequent
18 health risk assessment step.

19 The results obtained through a HMC method for the assessment of PCDD/Fs ground-level concen-
20 trations are compared to those obtained by a standard PMC approach, and both the transparency of
21 the EIA procedure and the communicability of results are discussed.

22 The manuscript is organized as follows: in Section 2 the equations used to model plant emissions
23 and ambient air concentrations are presented; the characterization of the input parameters uncer-
24 tainty for the development of HMC and PMC methods is illustrated in Section 3; Section 4 shows
25 the output of the two propagation methods and discusses their methodological implications; finally,
26 the advantages of the HMC method are drawn in the Conclusions. For completeness, the Appendix
27 Section A1 provides the basics of possibility theory and Section A2 presents the pure PMC method
28 for uncertainty propagation and its evolution to the Hybrid probabilistic-possibilistic Monte Carlo
29 method under conditions of scarce data availability.

30

31

32 **2. POLLUTANT AIR CONCENTRATIONS MODEL**

33 The contribution to the ambient air concentration C_{air} (fg m^{-3}) on an annual average basis can be
34 computed by multiplying an emission term Q (ng s^{-1}), which quantifies the mass flow rate of

1 PCDD/Fs released into the atmosphere, and an atmospheric dispersion factor DF ($\text{fg m}^{-3}/\text{ng s}^{-1}$),
2 which quantifies the ambient concentration per unit of mass flow rate:

3

$$4 \quad C_{\text{air}} = Q \cdot DF \quad (1)$$

5

6 Since the atmospheric dilution of the emission occurs at different extents depending on the distance
7 from the plant stack, C_{air} and DF are actually space-dependent and take different values, $C_{\text{air}}(x,y)$
8 $DF(x,y)$, at the receptors points located in the study domain, usually described by a Cartesian grid
9 centered on the plant stack.

10 Equation (1) follows a simplified approach for the assessment of C_{air} since it assumes that the
11 PCDD/Fs are emitted in the gas-phase only: this approach, although still providing realistic results,
12 reduces the complexity of the calculation model thus enabling the application of the uncertainty
13 propagation methods.

14 The emitted PCDD/Fs mass flow rate Q in equation (1) has been computed on the basis of the plant
15 daily throughput of waste, P ($\text{Mg}_{\text{waste}} \text{ day}^{-1}$), the PCDD/Fs concentration in the emitted flue gas, C_D
16 (ng m^{-3}), and the specific gas production V_F ($\text{m}^3 \text{ Mg}_{\text{waste}}^{-1}$):

17

$$18 \quad Q = \frac{P \cdot C_D \cdot V_F}{3600 \cdot 24} \quad (2)$$

19

20 As usual for this kind of evaluations (Van den Berg et al. 1998, US EPA 2005), the PCDD/Fs con-
21 centration is expressed in terms of equivalent toxicity mass per unit gas volume at normal condi-
22 tions (0° C , 101.3 kPa); coherently, the specific gas production refers to the same temperature and
23 pressure conditions.

24 The dispersion term DF in equation (1) has been computed by simulating the atmospheric transport
25 and dispersion of the emitted PCDD/Fs in the surroundings of the plant by means of the ISCST3
26 model (Industrial Source Complex – Short-term version 3). Formerly a US EPA regulatory model
27 for air dispersion modeling, this model is still regarded as a screening model for the assessment of
28 the impact on air quality of atmospheric emissions from industrial sources (US EPA, 1995).

29 Local meteorological conditions (wind speed and direction, ambient air temperature, atmospheric
30 stability), source features (stack height, flue gas speed and temperature, pollutant mass flow rate)
31 and geographical features of the area (terrain elevation, land use) are the basic input data for the
32 dispersion model. Output of the ISCST3 model is the 2D field of the contribution to the ground-
33 level concentration data in the study domain around the plant. Since in this model the output con-

1 concentrations are linearly proportional to the emitted flow rate, the dispersion term DF can be eva-
2 luated running the model for a unit mass flow rate (1 ng s^{-1}).
3 The DF values to be used in equation (1) for the estimation of the PCDD/Fs annual average concen-
4 tration have been obtained for the 1681 nodes of a Cartesian grid centered on the plant (250 m cell
5 spacing) through one-year long model simulations based on the hourly time series of locally meas-
6 ured meteorological data.

7
8

9 **3. UNCERTAINTY REPRESENTATION AND PROPAGATION**

10 The input parameters of the emission model (equation (2)) have been characterized as follows:

- 11 – the plant daily throughput P is a constant parameter whose value is assigned during project de-
12 sign; for the plant of this case study, P has been set to the value of $900 \text{ Mg}_{\text{waste}} \text{ day}^{-1}$;
- 13 – the PCDD/Fs concentration C_D is an uncertain parameter whose value varies during normal gasi-
14 fication operation due to the fluctuations of the process parameters and to the heterogeneous and
15 variable composition of the fed waste;
- 16 – the specific gas production V_F is an uncertain parameter. Although its value is usually set in the
17 plant design phase, actually V_F can present variations during plant operation caused by fluctuations
18 of the energy content of the fed waste as a consequence of its heterogeneous and variable composi-
19 tion.

20 Due to the rather limited applications of the waste gasification process, extended time series data-
21 sets containing C_D and V_F values collected during operation of similar plants are not available.

22 However, different studies have recently investigated the pollutant emission from waste gasification
23 plants (Klein 2002, Yamada et al. 2004, Porteous 2005, Arena 2012, University of California 2009).

24 From these studies, 35 C_D and four V_F values have been derived.

25 The availability of a statistically significant set of C_D average values, has allowed to represent the
26 uncertainty on this model parameter by means of a probability distribution. A Kolmogorov–
27 Smirnov’s test considering lognormal, Weibull, Beta, logistic PDFs has been performed in order to
28 properly choose the PDF best representative of the literature data. Figure 2 shows the selected Beta-
29 PDF of parameters $\alpha = 0.36$ and $\beta = 1.32$ and maximum value 0.07 ng m^{-3} , that is 30% less than the
30 regulatory limit of 0.1 ng m^{-3} (European Union, 2000).

31 Conversely, for V_F the available information (four literature values and the case study design value)
32 is very scarce. Thus, two different alternative representations of the uncertainty affecting V_F have
33 been considered:

1 – a subjective triangular PDF based on analyst judgment. The PDF range has been chosen to be
2 [3360, 6670] ($\text{m}^3 \text{Mg}_{\text{waste}}^{-1}$), which corresponds to the minimum and maximum values of the four
3 literature values, and its mode has been chosen to be $5420 \text{m}^3 \text{Mg}_{\text{waste}}^{-1}$, which corresponds to the
4 current case study design value (Figure 3);

5 – a triangular possibility distribution with the same range of the subjective PDF and most likely
6 value set equal to the case study design value (Figure 3).

7 Notice that, although the possibility and probability distributions used to represent the uncertainty
8 on V_F have similar shapes, they convey very different information: the possibility distribution
9 summarizes a set of cumulative distributions, bounded by the so-called Necessity and Possibility
10 functions (see Appendix a.1), whereas the subjective PDF defines just one specific cumulative dis-
11 tribution of that set.

12 On the other hand, model predictions of the DF values in equation (1) are also uncertain quantities
13 affected by i) the natural variability in the input parameters (such as meteorological variables and
14 source features), ii) measurement errors and iii) modeling errors due to the difficulties in capturing
15 the atmospheric behaviors (Sax and Isakov 2003, Rao 2005). Neglecting for simplicity the model
16 uncertainties, it turns out that the DF values are mainly affected by the variability in the meteoro-
17 logical input parameters, which largely exceeds the effect of the variability of flue gas temperature
18 and speed. In fact, the temperature is typically kept at a rather constant value during plant operation,
19 whereas the flue gas speed plays a negligible role on the atmospheric behavior of the emitted
20 plume. Here, the DF uncertainty has been estimated indirectly, by taking into account 10 different
21 years of local meteorological data and by separately running the dispersion model for each input da-
22 ta set: thus, 10 yearly DF values have been estimated for each grid node in the computation domain.
23 An example of the different wind conditions observed in the study area is given by the annual wind
24 roses reported in Figure 4 for four years out of the ten considered.

25 For illustration purposes, only one grid point has been considered for the uncertainty propagation,
26 chosen as the receptor most impacted by the plant emission (x_M, y_M), i.e. the grid node characterized
27 by the highest average of the 10 yearly DF values.

28 Due to the small dataset available, two alternative representations of the $DF(x_M, y_M)$ uncertainty
29 have been considered:

30 – a trapezoidal PDF based on analyst judgement with its minimum equal to 0, its core ranging be-
31 tween $5.69 \cdot 10^{-3}$ and $4.19 \cdot 10^{-2} \text{fg m}^{-3}/\text{ng s}^{-1}$, which corresponds to the minimum and maximum
32 values of the ten estimated DF values, and its maximum equal to $0.21 \text{fg m}^{-3}/\text{ng s}^{-1}$, which is the
33 DF obtained for the receptor point assuming the worst day conditions observed during the 10-
34 year period for atmospheric dispersion all year long (Figure 5);

1 – a trapezoidal possibility distribution with the same features of the subjective PDF (Figure 5).

2

3

4 **4. RESULTS**

5 With respect to the uncertainty propagation, the PMC method has been applied to the case in which
6 the uncertainty on C_D , V_F and $DF(x_M, y_M)$ are represented by the PDFs, whereas the HMC method
7 considers the PDF for C_D and the possibility distributions for V_F and $DF(x_M, y_M)$. The number m of
8 MC realizations of the parameters C_D , V_F and $DF(x_M, y_M)$ used in the PMC method has been set to
9 1000. The HMC procedure, instead, has been run considering $m = 1000$ realizations of the parame-
10 ter C_D and, for each of these realizations, 21 α -cut values (range 0-1, step 0.05) for the possibilistic
11 variables V_F and $DF(x_M, y_M)$.

12 The cumulative distributions of the model output variable, $C_{air}(x_M, y_M)$ obtained by applying the
13 PMC and HMC uncertainty propagation methods are presented in Figure 6. The PMC method pro-
14 vides a single cumulative distribution (continuous line), whereas the HMC model provides the be-
15 lief (lower dotted curve) and the plausibility (upper dashed curve) of the set $A = (-\infty, C_{air})$, which can
16 be interpreted as the boundary cumulative distributions of C_{air} at the receptor of coordinates $(x_M,$
17 $y_M)$.

18 As expected, the cumulative distribution of the model output obtained by the PMC is within the be-
19 lief and plausibility functions obtained by the hybrid approach.

20 Furthermore, the representation of the uncertainty on C_{air} provided by the PMC method appears to
21 be more concise and easy to be interpreted than the one provided by the HMC method. This is a
22 consequence of the different representation of the uncertainty on the input parameters V_F and
23 $DF(x_M, y_M)$: while the HMC method considers a set of cumulative distributions, the PMC forces all
24 the uncertainty on V_F and $DF(x_M, y_M)$ to be represented by single distributions. However, given the
25 scarcity of information available for the two parameters in this case study, the use of a specific PDF
26 seems unjustified.

27 Figure 6 also shows that the HMC method allows to process separately the uncertainty on C_D ,
28 represented by a probability distribution, from the uncertainty on V_F and DF , represented by possi-
29 bility distributions. These two contributions are explicitly visible in the results: in fact, the uncer-
30 tainty on C_D affects the slope of the belief and plausibility functions, while the distance between the
31 belief and plausibility functions reflects the lack of knowledge of the parameters V_F and DF . On the
32 other hand, in the PMC method the contributions of the input parameters uncertainties on the model
33 output are merged, giving rise to the slope of the output cumulative distribution.

1 Within the EIA procedure, for communication purposes, it is more effective to lump all the infor-
2 mation contained in the obtained cumulative distribution of C_{air} into a single value, such as for ex-
3 ample the β percentile. To this aim, setting a degree of confidence $\beta = 0.95$, the PMC method pro-
4 vides a single value, $C_{\text{air}}(x_M, y_M)^{95^{\text{th}}} = 2.80 \cdot 10^{-1} \text{ fg} \cdot \text{m}^{-3}$, representative of the 95th percentile of the
5 distribution of the PCDD/Fs annual average at the most impacted receptor point in the area. On the
6 contrary, with the HMC the 95th percentile is an uncertain quantity itself, whose true value lies in
7 the interval $[1.15 \cdot 10^{-2}, 5.65 \cdot 10^{-1}] \text{ fg} \cdot \text{m}^{-3}$, i.e. the 95th percentile of the Belief and Plausibility func-
8 tions. Table 2 reports the values of different percentiles for both PMC and HMC methods: PMC
9 values are always in the range of HMC values and the distance between the plausibility and belief
10 functions increases from lower to higher percentiles. Notice that for any percentile considered the
11 gap between the plausibility and the belief functions is in the range of one/two orders of magnitude:
12 the uncertainty on the VF and DF parameters appears to significantly affect the estimated ground
13 level concentrations. In this respect, the capability of the HMC method to separately process the
14 contribution of the different uncertainties gives rise to results that clearly show the effects of the
15 lack of knowledge on the input parameters. This is a desirable quality leading to more informative
16 and transparent outputs, also in the light of the subsequent calculations for health risk assessment.
17 It is worth noticing that the concentration estimates at the selected receptor for the most and the
18 least favourable year for atmospheric dispersion obtained by means of the traditional deterministic
19 approach are $0.03 \text{ fg} \cdot \text{m}^{-3}$ and $0.24 \text{ fg} \cdot \text{m}^{-3}$, respectively, thus varying by almost one order of magni-
20 tude. This means that the traditional deterministic approach based on just one single year simula-
21 tion, as is done in the common practice, can lead to either too precautionary or non-conservative es-
22 timates based on the arbitrary choice of the analyst about the reference year to be used in the model
23 simulation. In this respect, a preliminary assessment of the representativeness of the year chosen for
24 the weather model simulation or multi-year modelling are recommended for deterministic approach
25 calculations.

26 Finally, notice that both PMC and HMC methods have been applied under the simplifying assump-
27 tion of independence of the parameters C_D and V_F , although they are expected to be somehow cor-
28 related. Future developments of this work may thus include investigating the effects of the depend-
29 ence between these parameters on the uncertainty propagation results, for example resorting to the
30 approach suggested in (Pedroni and Zio 2012).

31

32

1 **5. CONCLUSION**

2 In this work the uncertainties in the first steps for the atmospheric emission and dispersion estima-
3 tion of an Environmental Impact Assessment (EIA) procedure have been treated by both a Hybrid
4 probabilistic and possibilistic Monte Carlo method (HMC) and a pure Probabilistic Monte-Carlo
5 method (PMC). Calculations have been performed for the case study of the project of a new waste
6 gasification plant, focusing on dioxin/furan emissions that are a primary concern for human health
7 due to their carcinogenic potential. The expected impact of the plant emissions has been quantified
8 in terms of the contribution to the annual average concentration of dioxins and furans in ambient air
9 at the most impacted receptor in the neighbourhood of the plant. The comparison between the re-
10 sults obtained by the HMC and PMC methods points out that the former is more effective in propa-
11 gating the input uncertainties through the model when little information is available for some input
12 parameters. In particular, i) the information provided by the output of the HMC method is more
13 consistent with that (little) available for the input parameters and ii) uncertainty is processed more
14 “transparently” than with PMC methods, avoiding arbitrary and subjective assumptions by the ana-
15 lyst on the input probability distribution functions and separating the contributions to the output un-
16 certainty due to the probabilistic and possibilistic input parameters.

17 This research has been conceived as a preliminary study to assess the potential for the implementa-
18 tion of HMC methods to the complete EIA procedure. In this regard, the satisfactory outcomes of
19 this first analysis foster future works towards the extension of the HMC method to the remaining
20 steps of an EIA procedure, i.e. the evaluation of the human exposure through the different impact
21 pathways and the subsequent risk assessment.

22 Finally, it is worth noticing that the principal users of the EIA findings are decision-makers often
23 responsible for communicating the results to the population living in the area of the planned instal-
24 lation. With respect to environmental and health-related issues, there is in general social aversion to
25 accept information expressed in terms of probability. Therefore, future studies will also have to in-
26 vestigate the way of post-processing the results of a whole EIA procedure developed within an hy-
27 brid probabilistic-possibilistic framework to make them communicable to the stakeholders and to
28 make them more easily understandable. To this purpose, the abilities of the HMC method to avoid
29 arbitrary assumptions and to provide results that explicitly report both probabilistic and possibilistic
30 uncertainties could be useful for a transparent and clear post-process.

31

32

33 **APPENDIX**

34 **A.1. BASIC OF POSSIBILITY THEORY**

1 In possibility theory, uncertainty is represented by a possibility function $\pi(y)$. For each y in a set
 2 Ω , $\pi(y)$ expresses the degree of possibility of y . When $\pi(y) = 0$ for some y , it means that the
 3 outcome y is considered an impossible situation. When $\pi(y) = 1$ for some y , it means that the out-
 4 come y is possible, i.e.: is just unsurprising, normal, usual (Dubois 2006). This is a much weaker
 5 statement than when probability is 1.

6 The possibility function gives rise to probability bounds, upper and lower probabilities, referred to
 7 as necessity and possibility measures (N, Π). The possibility of an event A , $\Pi(A)$, is defined by

$$\Pi(A) = \sup_{y \in A} \{\pi(y)\} \quad (\text{a.1})$$

8 and the necessity measure $N(A)$ is defined by:

$$N(A) = 1 - \Pi(\text{not}A) = 1 - \sup_{y \notin A} \{\pi(y)\}$$

9 Let $\mathcal{P}(\pi)$ be a family of probability distributions such that for all events A , $N(A) \leq P(A) \leq \Pi(A)$.
 10 Then,

$$N(A) = \inf P(A) \text{ and } \Pi(A) = \sup P(A) \quad (\text{a.2})$$

11 where *inf* and *sup* are with respect to all probability measures in \mathcal{P} . Hence the necessity measure is
 12 interpreted as a lower level for the probability and the possibility measure is interpreted as an upper
 13 limit. Referring to subjective probabilities, the bounds reflect that the analyst is not able or willing
 14 to precisely assign his/her probability, and the bounds are the best he/she can do given the informa-
 15 tion available; in other words, he or she can only describe a subset of \mathcal{P} which contains his/her
 16 probability (Dubois 2006).
 17

18 **A.2. PROBABILISTIC-POSSIBILISTIC UNCERTAINTY REPRESENTATION AND** 19 **PROPAGATION THROUGH A MODEL**

21 Let us consider a model whose output $Z = f(Y_1, Y_2, \dots, Y_n)$ is a function of n uncertain variables
 22 $Y_i, i = 1, \dots, n$. The uncertainties of the first k variables can be represented by probability distribu-
 23 tions $p_{Y_i}(y)$ properly derived from data, whereas for the remaining $n - k$ the scarcity of informa-
 24 tion provide a weaker statistical base for a specific probability assignment, making the construction
 25 of PDFs a critical operation. Two different approaches are here presented to represent and propa-
 26 gate such uncertainties
 27

28 **a. Pure probabilistic Monte-Carlo method (PMC)**

29 The uncertainties of all n input variables are treated in terms of probability distributions. Probabil-
 30 ity representations of the $n - k$ variables can be assigned i.e.: based on expert judgment. For exam-
 31 ple, let us considered a typical case in which the available information on a model parameter x is
 32 only that its values are located somewhere between a value x_{min} and a value x_{max} . In this case, a uni-
 33 form probability distribution $p(x) = 1/(x_{max} - x_{min}), \forall x \in [x_{min}, x_{max}]$ is typically assumed to repre-
 34 sent the uncertainty on x . This approach appeals to: i) Laplace principle of insufficient reason ac-
 35 cording to which all that is equally plausible is equally probable and to ii) the maximum entropy
 36 approach (Baraldi et al. 2010). However, doubts on the consistency of this uncertainty representa-
 37 tion have been raised (Baudrit et al. 2006) as it seems that the insufficient knowledge may justify
 38 choices of specific functional probability distributions, like the uniform, but it should somehow ac-
 39 count for the full set of possible probability distributions on $X = [x_{min}, x_{max}]$, so that the probability
 40 of value $x \in X$ is allowed to take any values in $[0,1]$ (Baraldi et al. 2010).

1 The PMC method then applies a single loop Monte Carlo simulation to propagate the uncertainties
2 of the n variables through the model. The operative steps of the propagation procedure are the fol-
3 lowing:

4 1 Sample the i -th realization (y_1^i, \dots, y_n^i) of the uncertain variables (Y_1, \dots, Y_n) from their respec-
5 tive PDFs $p_{Y_1}(y_1), \dots, p_{Y_n}(y_n)$

6 2 Compute the output of the model corresponding to the i -th realization of the uncertain va-
7 riables: $Z_i = f(y_1^i, \dots, y_n^i)$

8 3 Repeat steps 1 and 2 for many times. Then, derive the cumulative distribution $F(Z)$ from the
9 outputs $Z_i, i = 1, \dots, m$

10 The cumulative distribution $F(Z)$ obtained gives information on the output uncertainty. Setting a
11 percentile β , that corresponds to the desired degree of confidence, a concise output value of Z can
12 be provided. The output realizations $Z_i, i = 1, \dots, m$, found in step 2 can be directly used to compute
13 other lumped indicators of the output distribution, such as its mean and standard deviation values.

14 **b. Hybrid probabilistic-possibilistic Monte-Carlo method (HMC)**

15 In the Hybrid probabilistic-possibilistic method, the uncertainties of the $n - k$ variables are
16 represented in terms of possibility distributions $(\pi^{Y_{k+1}}, \dots, \pi^{Y_n})$.

17 Different methods have been developed to derive possibility distributions from the available infor-
18 mation (Baudrit & Dubois 2006, Dubois 1993). Often the analyst only knows that an uncertain vari-
19 able can take values in a given range $[a, b]$ wherein the most likely value is c . Triangular possibility
20 function with the range $|a, b|$ taken as base and c taken as vertex can be typically used to describe
21 this information. It has been shown that the family of probability distributions defined by such pos-
22 sibility distribution with contains all the probability distributions with support $[a, b]$ and mode c
23 (Baudrit & Dubois 2006).

24 In the HMC method, the propagation of the uncertainties expressed in terms of both PDFs and pos-
25 sibility curves is performed by combining the Monte Carlo technique with fuzzy interval analysis
26 (Baudrit et al. 2006). The operative steps of the propagation procedure are the following:

27 1 sample the i -th realization (y_1^i, \dots, y_k^i) of the random variable vector (Y_1, \dots, Y_k)

28 2 select a possibility value $\alpha \in [0, 1]$ and the corresponding α -cuts of the possibility distributions
29 $(\pi^{Y_{k+1}}, \dots, \pi^{Y_n})$, i.e.: the intervals of values of the possibilistic variables (Y_{k+1}, \dots, Y_n) with associated
30 possibility distributions greater or equal to α .

31 3 calculate the smallest and largest values of $f(y_1^i, \dots, y_k^i, Y_{k+1}, \dots, Y_n)$, denoted by \underline{f}_α^i and \overline{f}_α^i re-
32 spectively, considering the fixed values (y_1^i, \dots, y_k^i) sampled in 1. for the random variables

33 (Y_1, \dots, Y_k) and all values of the possibilistic variables (Y_{k+1}, \dots, Y_n) in the α -cuts of their possibil-
34 ity distributions $(\pi^{Y_{k+1}}, \dots, \pi^{Y_n})$ found in 2. Then, consider the extreme values \underline{f}_α^i and \overline{f}_α^i found in

35 3. as the lower and upper limit of the α -cut of $f(y_1^i, \dots, y_k^i, Y_{k+1}, \dots, Y_n)$

36 4 return to step 2. and repeat for another α -cut; the fuzzy random realization (fuzzy interval) π_i^f
37 of $Z = f(Y)$ is obtained as the collection of the values \underline{f}_α^i and \overline{f}_α^i for each α -cut

38 5 return to step 1. to generate a new realization of the random variables.

39 The procedure is repeated for $i = 1, \dots, m$: at the end of the procedure m realizations of fuzzy inter-
40 vals are obtained, i.e.: $(\pi_1^f, \dots, \pi_m^f)$.

1 For each set A contained in the universe of discourse U_z of the output variable Z , it is possible to
 2 obtain the possibility measure $\Pi_i^f(A)$ and the necessity measure $N_i^f(A)$ from the corresponding
 3 possibility distribution $\pi_i^f(z)$, by:

$$\Pi_i^f(A) = \max_{z \in A} \{\pi_i^f(z)\} \quad (\text{a.3})$$

$$N_i^f(A) = \inf_{z \notin A} \{1 - \pi_i^f(z)\} = 1 - \Pi_i^f(\bar{A}) \quad (\text{a.4})$$

$$\forall A \subseteq U_z$$

5 Finally, the m different realizations of possibility and necessity measures can be combined to obtain
 6 the belief $Bel(A)$ and the plausibility $Pl(A)$ for any set A , respectively (Baudrit et al. 2006):

$$Bel(A) = \sum_{i=1}^m \frac{N_i^f(A)}{m} \quad (\text{a.5})$$

$$Pl(A) = \sum_{i=1}^m \frac{\Pi_i^f(A)}{m} \quad (\text{a.6})$$

8 For each set A , this technique computes the belief and plausibility as the average of the possibility
 9 measures associated with each output fuzzy interval.

10 The likelihood of the value $f(Y)$ passing a given threshold z can then be computed by considering
 11 the belief and the plausibility of the set $A = (-\infty, z]$; in this respect, $Bel(f(Y) \in (-\infty, z])$ and

12 $Pl(f(Y) \in (-\infty, z])$ can be interpreted as bounding, average cumulative distributions

13 $\underline{F}(z) = Bel(f(Y) \in (-\infty, z])$, $\bar{F}(z) = Pl(f(Y) \in (-\infty, z])$ (Baudrit et al. 2006). Thus, one way to es-

14 timate the total uncertainty on $f(Y)$ is to provide a confidence interval at a given level of confi-

15 dence, taking the lower and upper bounds from $Pl(f(Y) \in (-\infty, z])$ and $Bel(f(Y) \in (-\infty, z])$, re-

16 spectively (Baudrit et al. 2006). Notice, however, that it is not possible to directly obtain

17 information on the mean and standard deviation of the output distribution from the plausibility and
 18 belief distributions.

19

20 REFERENCES

21

22 Arena, U., 2012. Process and technological aspects of municipal solid waste gasification. A review.
 23 *Waste Management* 32: 625–639

24

25 Aven, T. & Zio, E. 2011. Some considerations on the treatment of uncertainties in risk assessment
 26 for practical decision making. *Reliability Engineering and System Safety* 96: 64-74.

27

28 Baraldi, P. & Zio, E. 2008. A Combined Monte Carlo and Possibilistic Approach to Uncertainty
 29 Propagation in Event Tree Analysis. *Risk Analysis* 28: 1309-1326.

30

31 Baraldi, P., Popescu, I.C., Zio, E. 2010. Methods of Uncertainty Analysis in prognostics. *Internation-*
 32 *Journal of Performance Engineering* 6: 305-326

33

34 Baudrit, C. & Dubois, D. 2006. Practical Representations of Incomplete Probabilistic Knowledge.
 35 *Computational Statistics & Data Analysis* 51: 86-108.

1
2 Baudrit, C., Dubois, D., & Guyonnet, D. 2006. Joint Propagation of Probabilistic and Possibilistic
3 Information in Risk Assessment. *IEEE Transactions on Fuzzy Systems* 14: 593-608.
4
5 Domingo, J.L., Agramunt, M.C., Nadal, M., Schuhmacher, M., Corbella, J., 2002. Health risk
6 assessment of PCDD/PCDF exposure for the population living in the vicinity of a municipal waste
7 incinerator. *Archives Environmental Contamination Toxicology* 43: 461-465.
8
9 Dubois, D. 2006. Possibility theory and statistical reasoning. *Computational Statistics & Data*
10 *Analysis* 51: 47-69
11
12 European Union Council Directive 85/337/EEC of 27 June 1985 on the assessment of the effects of
13 certain public and private projects on the environment. *Official Journal L* 175, 5.7.1985.
14
15 European Union Council Directive 97/11/EC of 3 March 1997 amending Directive 85/337/EEC on
16 the assessment of the effects of certain public and private projects on the environment. *Official*
17 *Journal L* 73, 14.3.1997.
18
19 European Union Directive 2000/76/EC of the European Parliament and of the Council of
20 4 December 2000 on the incineration of waste. *Official Journal L* 332, 28.12.2000.
21
22 European Union Directive 2003/35/EC of the European Parliament and of the Council of 26 May
23 2003, providing for public participation in respect of the drawing up of certain plans and pro-
24 grammes relating to the environment and amending with regard to public participation and access to
25 justice Council Directives 85/337/EEC and 96/61/EC. *Official Journal L* 156, 25.6.2003.
26
27 Ferson, S. & Ginzburg, L. 1996. Different methods are needed to propagate ignorance and variabili-
28 ty. *Reliability Engineering and system safety* 54: 133-144.
29
30 Flage, R., Baraldi, P., Zio, E., Aven, T. 2010. Possibility-probability transformation in comparing
31 different approaches to the treatment of epistemic uncertainties in a fault tree analysis. In B. Ale,
32 I.A. Papazoglu, E. Zio (Eds.), *Reliability, Risk and Safety - Proceedings of the European Safety and*
33 *RELIability (ESREL) 2010 Conference, Rhodes, Greece, 714-721.*
34
35 García-Díaz, J.C, Gozalvez-Zafrilla, J.M. 2011. Uncertainty and sensitive analysis of environmental
36 model for risk assessments: An industrial case study. *Reliability Engineering and System Safety*
37
38 Guyonnet, D., Bourguine, B., Dubois, D., Fargier, H., Come, B., Chiles, J.P., 2003. Hybrid approach
39 for addressing uncertainty in risk assessments. *Journal of Environmental Engineering* 129: 68-78.
40
41 Guyonnet, D., Bellenfant, G., Bouc, O., 2008. Soft methods for treating uncertainties: applications
42 in the field of environmental risks. *Advances in Intelligent and Soft Computing* 48: 16-26.
43
44 Kentel, E., Aral, M.M., 2005. 2D Monte Carlo versus 2D fuzzy Monte Carlo health risk assessment.
45 *Stochastic Environmental Research and Risk Assessment* 19: 86-96
46
47 Klein, A. 2002. Gasification: An Alternative Process for Energy Recovery and Disposal of Municipi-
48 pal Solid Wastes. M.S. Thesis in Earth Resources Engineering, Columbia University.
49
50 Klir, G.J. & Yuan, B. 1995. *Fuzzy Sets and Fuzzy Logic: Theory and Applications*. Upper Saddle
51 River, NJ: Prentice-Hall.

1
2 Kumar, V., Montse, M., Schuhmacher, M., Domingo, J.L. 2009. Partitioning total variance in risk
3 assessment: Application to a municipal solid waste *incinerator*. *Environmental Modelling & Soft-*
4 *ware* 24: 247-261
5
6 Li, J., Huang, H.G., Zeng, G., Maqsood, I., Huang, Y. 2007. An integrated fuzzy-stochastic model-
7 ling approach for risk assessment of groundwater contamination. *Journal of Environmental Man-*
8 *agement* 82: 177-188.
9
10 Lonati, G., Cernuschi, S., Giugliano, M., Grosso, M., 2007. Health risk analysis of PCDD/F emis-
11 sions from MSW incineration: comparison of probabilistic and deterministic approaches. *Chemos-*
12 *phere* 67: S334-S343.
13
14 Lonati, G., Zanoni, F., 2012. Probabilistic health risk assessment of carcinogenic emissions from a
15 MSW gasification plant. *Environment International* 44: 80-91
16
17 Mukerjee, D., 1998. Health impact of polychlorinated dibenzo-p-dioxins: a critical review. *Journal*
18 *of the Air & Waste Management Association* 48: 157-165.
19
20 Pedroni, N., Zio, E., 2012. Empirical comparison of methods for the hierarchical propagation of hy-
21 brid uncertainty in risk assessment, in presence of dependences. *International Journal of Uncertain-*
22 *ty, Fuzziness and Knowledge-based Systems*.
23
24 Porteous, A., 2005. Why energy from waste incineration is an essential component of environmen-
25 tally responsible waste management. *Waste Management* 25: 451-459.
26
27 Rao, K.S., 2005 Uncertainty Analysis in Atmospheric Dispersion Modeling. *Pure and Applied*
28 *Geophysics* 162: 1893-1917.
29
30 Sax, T., Isakov, V., 2003. A case study for assessing uncertainty in local-scale regulatory air quality
31 modeling applications. *Atmospheric Environment* 37: 3481-3489.
32
33 Schuhmacher, M., Domingo, J.L., 2006. Long-term study of environmental levels of dioxins and
34 furans in the vicinity of a municipal solid waste incinerator. *Environment International* 32: 397-
35 404.
36
37 Schuhmacher, M., Meneses, M., Xifrò, A., Domingo J.L. 2001. The use of Monte-Carlo simulation
38 techniques for risk assessment: study of a municipal waste incinerator. *Chemosphere* 43: 787-799.
39
40 Sonnemann, G.W., Pla, Y., Schuhmacher, M., Castells, F. 2002. Framework for the uncertainty as-
41 sessment in The Impact Pathway Analysis with an application on a local scale in Spain. *Environ-*
42 *ment International* 28: 9-18.
43
44 Travis, C.C., Hattemer-Frey, H.A., 1991. Human exposure to dioxin. *The science of the total*
45 *environment* 104: 97-127.
46
47 University of California. 2009. Evaluation of Emission from Thermal Conversion Technology
48 Processing Municipal Solid Waste and Biomass. *Final report for BioEnergy producers Association*.
49

1 US EPA, 1995. User's guide for the Industrial Source Complex (ISC3) dispersion models. US Envi-
2 ronmental Protection Agency report EPA-454/B-95-003b.
3 (www.epa.gov/scram001/dispersion_alt.htm)
4

5 US EPA, 2005. Human health risk assessment for hazardous waste combustion facilities. Report
6 EPA/530/R-05/006, US EPA Office of Solid Wastes.
7

8 Van den Berg, M., Birnbaum, L., Bosveld, B.T.C., Brunström, B., Cook, P., Feeley, M., Giesy, J.P.,
9 Hanberg, A., Hasegawa, R., Kennedy, S.W., Kubiak, T., Larsen, J.C., van Leeuwen, F.X.R., Liem,
10 A.K.D., Nolt, C., Peterson, R.E., Poellinger, L., Safe, S., Schrenk, D., Tillitt, D., Tysklind, M.,
11 Younes, M., Waern, F., Zacharewski, T., 1998. Toxic Equivalency Factors (TEFs) for PCBs,
12 PCDDs, PCDFs for humans and wildlife. *Environmental Health Perspectives* 106: 775-792.
13

14 Yamada, S., Shimizu, M., Miyoshi, F. 2004. Thermostelected Waste Gasification and Reforming Proc-
15 ess. *JFE technical report* 3: 20-24.
16
17